



CENTRAL UNIVERSITY OF HARYANA
(Established vide Act No. 25 (2009) of Parliament)
Jant-Pali, Mahendergarh-123029


NOTICE INVITING QUOTATION NO. 16/2024

Name of Work: Provision of curing tank, Storage pits and false ceiling in Staff room etc. for Civil Engineering Laboratories/workshop at CUH.

Sealed percentage rate quotations are invited on behalf of Central University of Haryana, Mahendergarh for the work of "Provision of curing tank, Storage pits and false ceiling in Staff room etc. for Civil Engineering Laboratories/workshop at CUH". The quotation should reach the office of the Executive Engineer, Room No.-217, Administrative Building, CUH on or before 29/01/2024 upto 02:00 PM. The quotation shall be opened on the same day i.e. 29/01/2024 at 02:30 PM. The bidders may attend the said meeting on 29/01/2024.

The terms & conditions for the same are given below:

1. The BOQ is attached as **Annexure-'I'**.
2. The work will be carried out as per the satisfaction of the engineer in charge.
3. The agency/firm must deposit EMD of Rs. 2200/- (Rupees Two thousand two hundred only) in the form of NEFT/RTGS in favour of Central University of Haryana's Account No. 7824000100000392 IFSC Code: PUNB0782400 (Punjab National Bank, Jant-Pali, Mahendergarh).
4. The agency must submit the details of EMD submitted to CUH i.e. UTR details etc. along with bank account details of the agency/firm for the purpose of release of EMD of unsuccessful bidders.
5. Copy of GST registration certificate and PAN Card of the agency is required to be enclosed along with quotation.
6. Validity of the quotations will be 60 days from the date of opening.
7. The rate includes all taxes like GST, and other taxes and carriage of the material etc.
8. Time of completion of work will be 30 days.
9. No advance payment will be made.
10. Conditional quotations will not be considered.
11. The agency should inspect the site before quoting the rate.
12. The quantity of items in BOQ is tentative which may change depending upon site conditions.
13. The agency should provide proper safety tools to its workers. The CUH will not be responsible for any accident.
14. Time is the main essence of the contract. Hence, an appropriate penalty upto 10% maximum can be imposed on the agency for delayed completion of work.
15. No labor below the age of 18 years be employed on site.
16. All T&P required will be arranged by the contractor.
17. The agency/Contractor shall make its own arrangement of electricity, if required.
18. Security deposit @5% and necessary recoveries i.e. GST, Labour Cess and Income Tax etc. will be recovered from the bills of the contractor.


Executive Engineer

BOQ

Name of Work: Provision of curing tank, Storage pits and false ceiling in Staff room etc. for Civil Engineering Laboratories/workshop at CUH.

Item No.	Description of item	Qty	Unit	Rate	Amount
1	Earth work in excavation by mechanical means (Hydraulic excavator) /manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil.	5.40	cum	286.85	1548.99
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:5:10 (1 cement : 5 coarse sand (zone-III) derived from natural sources : 10 graded stone aggregate 40 mm nominal size derived from natural sources)	1.61	cum	6050.65	9741.55
3	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:6 (1 cement : 6 coarse sand)	4.50	cum	6658.25	29962.13
4	Cement plaster (1:3) finished with a floating coat of neat cement. 20 mm Cement Plaster	46.40	Sqm.	507.85	23564.24
5	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	2.64	sqm	545.00	1438.80
6	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundations and plinth in : cement mortar 1:4 (1 cement : 4 coarse sand)	3.60	sqm.	837.85	3016.26
7	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1 Cement : 3 coarse sand (zone-III) derived from natural sources : 6 graded stone aggregate 20 mm nominal size derived from natural sources)	1.60	cum	6833.40	10933.44

8	Neat cement punning.	1.60	Sqm.	67.80	108.48
9	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete	42.00	Kg	93.05	3908.10
10	<p>Providing and Fixing 15 mm thick densified tegular edged eco friendly light weight calcium silicate false ceiling tiles of approved texture of size 595 x 595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38 mm made from 0.33 mm thick (minimum) sheet, spaced 1200 mm centre to centre, and cross "T" of size 24x28 mm made out of 0.33 mm (Minimum) sheet, 1200 mm long spaced between main 'T' at 600 mm centre to centre to form a grid of 1200x600 mm and secondary cross 'T' of length 600 mm and size 24 x28 mm made of 0.33 mm thick (Minimum) sheet to be inter locked at middle of the 1200x 600 mm panel to from grid of size 600x600 mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size(24x24X3000 mm made of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450 mm centre to centre with 25 mm long dry wall screws @ 230 mm interval and laying 15 mm thick densified edges calicum silicate ceiling tiles of approved texture in the grid, including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc., wherever required. Main 'T' runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm G.I. adjustable rods with galvanised steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200 mm centre to centre along main 'T', bottom exposed with 24 mm of all Tsections shall be pre-painted with polyster baked paint, for all heights, as per specifications, drawings and as directed by Engineer-in-Charge.</p> <p>Note :- Only calcium silicate false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs) having area less than 0.30 sqm. The calcium silicate</p>	15.00	Sqm.	1718.70	25780.50

	ceiling tile shall have NRC value of 0.50 (Minimum), light reflection > 85%, non-combustible as per B.S. 476 part IV, 100% humidity resistance and also having thermal conductivity <0.043 w/mK.				
	Total (A)				110002.48
	Say Rs.				1,10,002/-
	% Above/Below				
	Quoted amount in Rupees				

Signature & stamp of Contractor/Agency

Handwritten initials

Handwritten signature and stamp